

856 Ship Notice/Manifest

X12/V4010/856: 856 Ship Notice/Manifest

Version: 2.0 Final

Author: Insight Direct USA, Inc.
Modified: 05/18/2006

856 Ship Notice/Manifest

Functional Group=SH

This Draft Standard for Trial Use contains the format and establishes the data contents of the Ship Notice/Manifest Transaction Set (856) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to list the contents of a shipment of goods as well as additional information relating to the shipment, such as order information, product description, physical characteristics, type of packaging, marking, carrier information, and configuration of goods within the transportation equipment. The transaction set enables the sender to describe the contents and configuration of a shipment in various levels of detail and provides an ordered flexibility to convey information. The sender of this transaction is the organization responsible for detailing and communicating the contents of a shipment, or shipments, to one or more receivers of the transaction set. The receiver of this transaction set can be any organization having an interest in the contents of a shipment or information about the contents of a shipment.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BSN	Beginning Segment for Ship Notice	M	1			Must use
040	DTM	Date/Time Reference	O	10			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
120	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12			Must use
150	REF	Reference Identification	O	>1			Used
LOOP ID - N1					200		
220	N1	Name	O	1			Must use
230	N2	Additional Name Information	O	2			Used
240	N3	Address Information	O	2			Used
250	N4	Geographic Location	O	1			Used
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
050	PRF	Purchase Order Reference	O	1			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
060	PO4	Item Physical Details	O	1			Must use
150	REF	Reference Identification	O	>1			Must use
190	MAN	Marks and Numbers	O	>1			Must use

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
060	PO4	Item Physical Details	O	1			Must use
150	REF	Reference Identification	O	>1			Must use
190	MAN	Marks and Numbers	O	>1			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
020	LIN	Item Identification	O	1			Must use
030	SN1	Item Detail (Shipment)	O	1			Must use
150	REF	Reference Identification	O	>1			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		N3/010	Used
020	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use

Description: Code to identify the type of information in the Authorization Information

Code Name

00 No Authorization Information Present (No Meaningful Information in I02)

ISA02	I02	Authorization Information	M	AN	10/10	Must use
-------	-----	----------------------------------	---	----	-------	----------

Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)

ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
-------	-----	---------------------------------------	---	----	-----	----------

Description: Code to identify the type of information in the Security Information

Code Name

00 No Security Information Present (No Meaningful Information in I04)

ISA04	I04	Security Information	M	AN	10/10	Must use
-------	-----	-----------------------------	---	----	-------	----------

Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)

ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	---------------------------------	---	----	-----	----------

Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

All valid standard codes are used.

ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
-------	-----	------------------------------	---	----	-------	----------

Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element

ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	---------------------------------	---	----	-----	----------

Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

Code Name

01 Duns (Dun & Bradstreet)

Insight Note :

Insight Test Id Qualifier

12 Phone (Telephone Companies)

Insight Note :

Code Name

Insight Production Id Qualifier

ISA08 I07 **Interchange Receiver ID** M AN 15/15 Must use

Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them

Insight Note : *Test ID: 6309246701T
Production ID: 6309246701*

ISA09 I08 **Interchange Date** M DT 6/6 Must use

Description: Date of the interchange

ISA10 I09 **Interchange Time** M TM 4/4 Must use

Description: Time of the interchange

ISA11 I10 **Interchange Control Standards Identifier** M ID 1/1 Must use

Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer

All valid standard codes are used.

ISA12 I11 **Interchange Control Version Number** M ID 5/5 Must use

Description: Code specifying the version number of the interchange control segments

Code Name

00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997

ISA13 I12 **Interchange Control Number** M N0 9/9 Must use

Description: A control number assigned by the interchange sender

ISA14 I13 **Acknowledgment Requested** M ID 1/1 Must use

Description: Code sent by the sender to request an interchange acknowledgment (TA1)

All valid standard codes are used.

ISA15 I14 **Usage Indicator** M ID 1/1 Must use

Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information

Code Name

P Production Data

T Test Data

ISA16 I15 **Component Element Separator** M 1/1 Must use

Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use
Description: Code identifying a group of application related transaction sets						
Code Name						
SH Ship Notice/Manifest (856)						
GS02	142	Application Sender's Code	M	AN	2/15	Must use
Description: Code identifying party sending transmission; codes agreed to by trading partners						
GS03	124	Application Receiver's Code	M	AN	2/15	Must use
Description: Code identifying party receiving transmission; codes agreed to by trading partners						
Insight Note : Test ID: 6309246701T Production ID: 6309246701						
GS04	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD						
GS05	337	Time	M	TM	4/8	Must use
Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)						
GS06	28	Group Control Number	M	NO	1/9	Must use
Description: Assigned number originated and maintained by the sender						
GS07	455	Responsible Agency Code	M	ID	1/2	Must use
Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480						
Code Name						
X Accredited Standards Committee X12						
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		<u>Code</u> <u>Name</u>				
	004010	Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997				

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use
Description: Code uniquely identifying a Transaction Set						
Code Name						
856 Ship Notice/Manifest						
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

BSN Beginning Segment for Ship Notice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

User Option (Usage): Must use

To transmit identifying numbers, dates, and other basic data relating to the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BSN01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
		Description: Code identifying purpose of transaction set				
		Code Name				
		00 Original				
BSN02	396	Shipment Identification	M	AN	2/30	Must use
		Description: A unique control number assigned by the original shipper to identify a specific shipment				
BSN03	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BSN04	337	Time	M	TM	4/8	Must use
		Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				
BSN05	1005	Hierarchical Structure Code	O	ID	4/4	Used
		Description: Code indicating the hierarchical application structure of a transaction set that utilizes the HL segment to define the structure of the transaction set				
		Code Name				
		0001 Shipment, Order, Packaging, Item				

Insight Note :

Only one shipment is allowed per 856.
 Only one Insight PO is allowed per 856.

Example:

BSN*00*020609336001*20060425*2210*0001~

DTM Date/Time Reference

Pos: 040	Max: 10
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

Code Name

011 Shipped

DTM02	373	Date	X	DT	8/8	Used
-------	-----	------	---	----	-----	------

Description: Date expressed as CCYYMMDD

DTM03	337	Time	X	TM	4/8	Used
-------	-----	------	---	----	-----	------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

DTM04	623	Time Code	O	ID	2/2	Used
-------	-----	-----------	---	----	-----	------

Description: Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow

Code Name

- CT Central Time
- ET Eastern Time
- MT Mountain Time
- PT Pacific Time
- UT Universal Time Coordinate

Example:

*DTM*011*20060425*1015*ET~*

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
<u>Code</u> <u>Name</u>						
S Shipment						

Example:

HL*1**S~

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 120	Max: 12
Detail - Optional	
Loop: HL	Elements: 4

User Option (Usage): Must use

To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD502	66	Identification Code Qualifier	X	ID	1/2	Used
<p>Description: Code designating the system/method of code structure used for Identification Code (67)</p> <p>Code Name</p> <p>2 Standard Carrier Alpha Code (SCAC)</p> <p>Insight Note : <i>This is not required if TD512 = ZZ</i></p>						
TD503	67	Identification Code	X	AN	2/80	Used
<p>Description: Code identifying a party or other code</p> <p>Insight Note : <i>Must use if product was physically shipped. This is not required if TD512 = ZZ.</i></p>						
TD505	387	Routing	X	AN	1/35	Used
<p>Description: Free-form description of the routing or requested routing for shipment, or the originating carrier's identity</p>						
TD512	284	Service Level Code	X	ID	2/2	Must use
<p>Description: Code indicating the level of transportation service or the billing service offered by the transportation carrier</p> <p>Code Name</p> <p>3D Three Day Service</p> <p>CG Ground</p> <p>CX Express Service</p> <p>G2 Standard Service</p> <p>IX Express Service - Worldwide</p> <p>ND Next Day Air</p> <p>NM Next Morning</p> <p>ON Overnight</p> <p>PB Priority Mail</p> <p>PC Primary Service Area - Next Day By 9:30 AM</p> <p>R5 Manifest Freight</p> <p>SA Same Day</p> <p>SC Second Day Air</p> <p>SD Saturday</p> <p>SG Standard Ground</p> <p>ST Standard Class</p>						

<u>Code</u>	<u>Name</u>
ZZ	Mutually Defined

Insight Note :
Use this for deliveries with no physical carrier. (Warranties and Software License no-media)

Insight Note :
If there is no physical shipment (no carrier), TD502 and TD503 are not used. TD512 must be set to 'ZZ'.

Example:
`TD5**2*FDE**FedEx Ground*****CG~`

If there is no physical carrier (Warranty or software license no-media orders), use this:
`TD5*****ZZ~`

REF Reference Identification

Pos: 150	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

BM Bill of Lading Number

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Example:

REF*BM*03291148~

N1 Name

Pos: 220	Max: 1
Detail - Optional	
Loop: N1	Elements: 4

User Option (Usage): Must use

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

Insight Note : *Ship to and Ship From are both required.*

Code Name

SF Ship From

Insight Note :

This is the actual location the product was shipped from.

ST Ship To

N102	93	Name	X	AN	1/60	Used
------	----	-------------	---	----	------	------

Description: Free-form name

N103	66	Identification Code Qualifier	X	ID	1/2	Used
------	----	--------------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

Code Name

92 Assigned by Buyer or Buyer's Agent

Insight Note :

Used with the Ship To (N101 = ST)

93 Code assigned by the organization originating the transaction set

Insight Note :

Used with the Ship From (N101 = SF)

N104	67	Identification Code	X	AN	2/80	Used
------	----	----------------------------	---	----	------	------

Description: Code identifying a party or other code

Insight Note : *If N101 = ST, this code should be the code that was sent on the 850.*

Example:

*N1*SF*VENDOR NAME*93*12345*

*N1*ST*CUSTOMER NAME*92*0000123456~*

N2 Additional Name Information

Pos: 230	Max: 2
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify additional names or those longer than 35 characters in length

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/60	Must use
		Description: Free-form name				
N202	93	Name	O	AN	1/60	Used
		Description: Free-form name				

Example:

N2*ADDITIONAL NAME INFO~

N3 Address Information

Pos: 240	Max: 2
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

Example:

*N3*STREET ADDRESS1*STREET ADDRESS2~*

N4 Geographic Location

Pos: 250	Max: 1
Detail - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Used
		Description: Code identifying the country				

Example:

*N4*CITY*ST*10011*USA~*

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
<u>Code</u> <u>Name</u>						
O Order						

Example:

HL*2*1*O~

PRF Purchase Order Reference

Pos: 050	Max: 1
Detail - Optional	
Loop: HL	Elements: 3

User Option (Usage): Must use

To provide reference to a specific purchase order

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PRF01	324	Purchase Order Number	M	AN	1/22	Must use
Description: Identifying number for Purchase Order assigned by the orderer/purchaser						
PRF04	373	Date	O	DT	8/8	Must use
Description: Date expressed as CCYYMMDD						
PRF07	92	Purchase Order Type Code	O	ID	2/2	Must use
Description: Code specifying the type of Purchase Order						
Insight Note : <i>This must match the PO type on the 850.</i>						
Code Name						
DS Dropship						
SA Stand-alone Order						

Insight Note :

Only one Insight PO is allowed per 856.

Example:

*PRF*4999999***20060513***DS~*

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
<u>Code</u> <u>Name</u>						
T Shipping Tare						

Insight Note :

This level is mandatory if shipping on pallets. If pallets are not used, do not send this HL loop.

Example:

HL *3*2*T~

PO4 Item Physical Details

Pos: 060	Max: 1
Detail - Optional	
Loop: HL	Elements: 9

User Option (Usage): Must use

To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO402	357	Size	X	R	1/8	Used
		Description: Size of supplier units in pack				
PO403	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		<u>Code</u> <u>Name</u>				
		EA Each				
PO405	187	Weight Qualifier	O	ID	1/2	Used
		Description: Code defining the type of weight				
		<u>Code</u> <u>Name</u>				
		G Gross Weight				
PO406	384	Gross Weight per Pack	X	R	1/9	Used
		Description: Numeric value of gross weight per pack				
PO407	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		<u>Code</u> <u>Name</u>				
		LB Pound				
PO410	82	Length	X	R	1/8	Used
		Description: Largest horizontal dimension of an object measured when the object is in the upright position				
PO411	189	Width	X	R	1/8	Used
		Description: Shorter measurement of the two horizontal dimensions measured with the object in the upright position				
PO412	65	Height	X	R	1/8	Used
		Description: Vertical dimension of an object measured when the object is in the upright position				
PO413	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				

<u>Code</u>	<u>Name</u>
IN	Inch

Example:

*PO4**36*EA**G*32*LB***48*48*60*IN~*

REF Reference Identification

Pos: 150	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Must use

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

2I Tracking Number

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Example:

REF*2I*12345678~

MAN Marks and Numbers

Pos: 190	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Must use

To indicate identifying marks and numbers for shipping containers

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Must use
Description: Code specifying the application or source of Marks and Numbers (87)						
Code Name						
GM SSCC-18 and Application Identifier						
MAN02	87	Marks and Numbers	M	AN	1/48	Must use
Description: Marks and numbers used to identify a shipment or parts of a shipment						

Example:

MAN*GM*850440000000000001~

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
<u>Code</u> <u>Name</u>						
P Pack						

Insight Note :

This level is mandatory if physical product is shipped in cartons.

Example:

HL*4*3*P~

PO4 Item Physical Details

Pos: 060	Max: 1
Detail - Optional	
Loop: HL	Elements: 9

User Option (Usage): Must use

To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO402	357	Size	X	R	1/8	Used
Description: Size of supplier units in pack						
Insight Note : <i>This is the quantity in the box.</i>						
PO403	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
Code Name						
EA Each						
PO405	187	Weight Qualifier	O	ID	1/2	Must use
Description: Code defining the type of weight						
Code Name						
G Gross Weight						
PO406	384	Gross Weight per Pack	X	R	1/9	Must use
Description: Numeric value of gross weight per pack						
PO407	355	Unit or Basis for Measurement Code	X	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
Code Name						
LB Pound						
PO410	82	Length	X	R	1/8	Used
Description: Largest horizontal dimension of an object measured when the object is in the upright position						
PO411	189	Width	X	R	1/8	Used
Description: Shorter measurement of the two horizontal dimensions measured with the object in the upright position						
PO412	65	Height	X	R	1/8	Used
Description: Vertical dimension of an object measured when the object is in the upright position						
PO413	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		<u>Code</u> <u>Name</u>				
		IN Inch				

Example:

*PO4**6*EA**G*2*LB***5*6*7*IN~*

REF Reference Identification

Pos: 150	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Must use

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

2I Tracking Number

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Insight Note : For small parcel carriers, this will be the tracking number. For LTL, this will be the bill of lading or waybill number.

Example:

REF*2I*12345678~

MAN Marks and Numbers

Pos: 190	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Must use

To indicate identifying marks and numbers for shipping containers

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Must use
Description: Code specifying the application or source of Marks and Numbers (87)						
Code Name						
GM SSCC-18 and Application Identifier						
MAN02	87	Marks and Numbers	M	AN	1/48	Must use
Description: Marks and numbers used to identify a shipment or parts of a shipment						

Example:

MAN*GM*850440000000000021~

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
<u>Code</u> <u>Name</u>						
I Item						

Insight Note :

This level is required.

Example:

HL*5*4*I~

LIN Item Identification

Pos: 020	Max: 1
Detail - Optional	
Loop: HL	Elements: 5

User Option (Usage): Must use

To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN01	350	Assigned Identification	O	AN	1/20	Must use
<p>Description: Alphanumeric characters assigned for differentiation within a transaction set</p> <p>Insight Note : <i>This is the line item number from the original Purchase Order. This number must match the line item number on the original purchase order.</i></p>						
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use
<p>Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)</p> <p>Code Name BP Buyer's Part Number</p>						
LIN03	234	Product/Service ID	M	AN	1/48	Must use
<p>Description: Identifying number for a product or service</p>						
LIN04	235	Product/Service ID Qualifier	X	ID	2/2	Must use
<p>Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)</p> <p>Code Name VP Vendor's (Seller's) Part Number</p>						
LIN05	234	Product/Service ID	X	AN	1/48	Must use
<p>Description: Identifying number for a product or service</p>						

Example:

LIN*00001*BP*5597676*VP*PY993UA#ABA~

SN1 Item Detail (Shipment)

Pos: 030	Max: 1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Must use

To specify line-item detail relative to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SN102	382	Number of Units Shipped	M	R	1/10	Must use
Description: Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set						
SN103	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
<u>Code</u> <u>Name</u>						
EA Each						

Example:

SN1**3*EA~

REF Reference Identification

Pos: 150	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

BB Authorization Number

Insight Note :

*Must be used for Software License Orders if Microsoft product, or if this number was sent on the original 850.
Must be used for Warranty Orders.*

SE Serial Number

Insight Note :

*Must be used if the product is serialized.
Must be used for Warranty Orders.*

PLA Product Licensing Agreement Number

Insight Note :

Must be used for Software License Orders

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Insight Note :

There can only be one Authorization Number (REF01=BB) and one Product Licensing Agreement Number (REF01=PLA) per line item.

There can be multiple serial numbers (REF01=SE) per line item number.

Example:

If a line item has a quantity of 3 and the product is serialized, 3 REF segments should be sent.

REF*SE*2UA6140H4V~
REF*SE*2UA6140H3Z~
REF*SE*2UA6140H5A~

If the line item has a quantity of 5, and is a software license, there should only be one authorization number and one product license agreement number sent for that line item.

REF*BB*123456LKP~
REF*PLA*9999234553DWE~

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Used

To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

Example:

CTT*402~

SE Transaction Set Trailer

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	NO	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
		Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element				
GE02	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	NO	1/5	Must use
		Description: A count of the number of functional groups included in an interchange				
IEA02	I12	Interchange Control Number	M	NO	9/9	Must use
		Description: A control number assigned by the interchange sender				